

## Specifications:

**Diffuser:** Acrylic, optional perf overlay

**Body:** Steel

**Finish:** See below

**Ballast:** Electronic, 120v, 277v, 347v, UNV (120/277v)

**Mounting:** Directly to standard J-box

**Dimming:** 0-10v option available

**Warranty:** 1 year limited warranty

**Listing :** Damp location



## Maximum wattage information:

Size	Max Wattage	Lamping
12"	52w	CFL
12"	36w	GU24
12"	120w	A19

Decorative wall sconce with choice of lens, finish, accent and lamping options. Suitable for a variety of applications: Corridors, entry ways, offices, living rooms and more

## Dimensions:

Model	Height	Width	Depth
ADA2412	11.5"	10"	3.875"



## ORDERING INFORMATION

Example: ADA2412-2-26Q-WA-BN-FPERF-UNV

MODEL #	# LAMPS	WATTAGE	OPTIONS	BALLAST
ADA2412	1	13Q – 13w quad 4-pin	<b>LENS</b>	UNV – 120/277V
	2	18Q – 18w quad 4-pin	WA – white acrylic	347 – 347v
		26Q – 26w quad 4-pin	WFA – white faux alabaster	DMMK10– 0-10V dimming – 2 wire
		26T – 26w triple tube 4-pin	<b>FINISH</b>	DMMK7 0 0-10v dimming – 4 wire
		32T – 32w triple tube 4-pin	PB – polished brass	
		2GU24 – 2 X GU24 (MAX 18W)	BN – brushed nickel	
		2xE26 – 2x60w max A19 E26	AB – antique brass*	
			ORB – oil rubbed bronze	
			<b>Accents</b>	
			CDB – centre double band	
			FPRF – full steel perf	
			CPRF – centre steel perf/bands	

Legend: **Q** quad tube 4-pin electronic, **T** triple tube 4-pin electronic, **2GU24** 2xGU24; **2xE26** 2x60w A19 med base



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	