

## Specifications:



**Body:** Steel

**Diffuser:** White acrylic or polycarbonate

**Finish:** Powder coated gloss white back pan

**Ballast:** Electronic, 120v, 277v, 347v, UNV (120/277v)

**Mounting:** Directly to standard J-box

**Warranty:** 1 year

**Listing :** Dry location



## Maximum wattage information:

Size	Max Wattage
12"	26w
17"	84w
21"	96w

Low profile fixture available in three sizes and many compact fluorescent lamp configurations. Also available with polycarbonate lens and tamper proof options. Suitable for a variety of applications: Corridors, entry ways, kitchens, offices, bedrooms, dorms and more

## Dimensions:

Model	Diameter	Depth
CM1312	12"	3"
CM1317	17"	3.6"
CM1821	21"	4.0"



We Ship to the U.S.A.



## ORDERING INFORMATION

Example: CM1317-2-26Q-WA -UNV

MODEL #	LAMPS	WATTAGE	OPTIONS	BALLAST
CM1312	1	13TT – 13w mag twin tube	WA – white acrylic	M(X) – magnetic, (N) NPF, (F) HPF
CM1317	2	13Q – 13w electronic quad tube	P – polycarbonate	UNV – 120/277v
CM1321	3	18Q – 18w electronic quad tube	WH - white	347 – 347v
		26Q – 26w electronic quad tube	BN – brushed nickel	DMADVMK10 – Advance Mark 10 2-wire dimming
		32T – 32w electronic triple tube	ORB – oil rubbed bronze	DMADVMK7 – Advance Mark 7 4-wire dimming
		42T – 42w electronic triple tube		
			T – tamper proof	
			ALUM – aluminum body	
			GSK – gasket	

Legend: **TT** – twin tube magnetic; **Q** quad tube 4-pin electronic, **T** triple tube 4-pin electronic



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	