

CM-17



This product features a white acrylic lens as standard. An optional white polycarbonate lens is available for high risk applications.

Fixture Type	Model No	Job Reference /Location	Lamp Type/Lamp

Model	Lamps	Watts/Lamp	Ballast	Options
CM-17-11	1	13 W TT	N-NPF	P-Polycarb
CM-17-14	2	13Q	F-HPF	T-Tamper Proof
CM-17-19	3	18Q	E-Electronic	
	4	26Q	ED-Dimming	
		18T	V2-277V	
		26T	V3-347V	
		32T		
		42T		

SPECIFICATIONS

Max Watt: 78W
Body: Steel
Finish: Powder Coated Gloss White
Diffuser: White Acrylic
Lamps: Q Quad Tube - 4 Pin, T Triple Tube - 4 Pin, TT Twin Tube - 2 Pin
Ballast: Electronic 4 Pin Lamp - Magnetic 2 Pin Lamp

Model	Diam	Max Watt	Depth/Proj.	
CM-17-11	11" and 10.12" Pan Dia.	26W	5.3"	Ballasts: 120V, fixtures supplied with NPF magnetic, HPF magnetic, HPF high frequency electronic ballasts. Mechanical: Fixtures mount directly to an outlet box. Approval: CSA NRTL/C
CM-17-14	14" and 12.75" Pan Dia.	64W	5.5"	
CM-17-19	19" and 17" Pan Dia.	126W	5.5"	

