


CM-20



Fixture Type	Model No	Job Reference /Location	Lamp Type/Lamp

Model	Lamps	Watts/Lamp	Ballast	Options
CM-20-11	1	13 W TT	N-NPF	P-Polycarb
CM-20-14	2	13Q	F-HPF	T-Tamper Proof
CM-20-19	3	18Q	E-Electronic	
	4	26Q	ED-Dimming	
			V2-277V	
			V3-347V	

Features a white acrylic lens as standard. An optional white polycarbonate lens is available for high risk applications.

SPECIFICATIONS

Max Watt: 72W
Body: Steel
Finish: Powder Coated Gloss White
Diffuser: White Acrylic
Lamps: Q Quad Tube - 4 Pin, T Triple Tube - 4 Pin, TT Twin Tube - 2 Pin
Ballast: Electronic 4 Pin Lamp - Magnetic 2 Pin Lamp

Model	Width	Max Watt	Depth/Proj.	Ballasts: 120V, fixtures supplied with NPF magnetic, HPF magnetic, HPF high frequency electronic ballasts. Mechanical: Fixtures mount directly to an outlet box. Approval: CSA NRTL/C
CM-20-11	11"	26W	2.8" and 11" Len	
CM-20-14	14"	52W	3.13" and 14" Len	
CM-20-19	19"	78W	4.13" and 19" Len	

