

Specifications:

- LED:** Samsung/Philips LEDs
- CRI:** Min 80
- Body:** Steel, powder coated gloss white
- Diffuser:** Acrylic
- Finish:** Cured painted process or plated options
- Driver:** 15"-Triac standard; 20" & 25" 0-10v dimming
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** Dry location



Mushroom lens



Flat lens



Flat lens w/ perf trim

LED information:

Size	Wattage	Lumens	Efficacy
15"	13.3	1641	123.3
15"	21.9	2781	126.9
20"	21.9	2781	126.9
20"	25	3500	125.0
25"	28	4000	142.8
25"	40	5000	125.0

Dimensions:

Model	Diameter	Depth
LFM0715-MRL	15"	3.6"
LFM0720-MRL	20.75"	4.0"
LFM0725-MRL	24"	4.5"

*Flat lens depth is 3"

ORDERING INFORMATION

Example: LFM0720-2781L-40K-MRL-CH-UNV

Split ring flush mount utilizing LED technology. Available in three sizes with choice of lumens outputs. Features a white acrylic lens in flat or mushroom and solid split ring outer trim. Option perforated of solid inlay trim. Suitable for a variety of applications: Corridors, entry ways, kitchens, offices, bedrooms and more



We Ship to the U.S.A.



MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LFM0715	1641L – 13.3w, 1641L	30K – 3000K	LENS	UNV – 120/277v **
	2781L – 21.9w, 2781L	35K – 3500K	MRL-mushroom white acrylic	347 – 347v 0-10v dimming
		40K – 4000K	FLT-flat white acrylic	DM0-10 – 0-10V dimming
LFM0720	2781L – 21.9w, 2781L 3500L – 25w, 3500L	50K – 5000K	FINISH -cured	**15" standard Triac dimming
			CBN-cured brushed nickel	**20" & 25" standard 0-10v dimming
			CCH- cured chrome	
LFM0725	4000L – 28w, 4000L 5000L – 40w, 5000L		CAB-cured antique brass	MS – motion sensor
			CORB-cured oil rubbed bronze	
			TRIM	FINISH -PLATED
			PERF-perf inlay	BNP-brushed nickel plated
			SOL-solid inlay	CHP-chrome plated
				ABP-antique brass plated
			SF – 9" semi-flush rod/canopy	ORBP-oil rubbed bronze plated



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	