

## Specifications:

- LED:** Samsung or Philips LED
- CRI:** Min 80
- Body:** Steel
- Diffuser:** White acrylic
- Finish:** See options
- Driver:** Standard Triac dimming; 0-10v available
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** Damp location; cCSAus



## LED information:

Size	Lumens	Wattage	Efficacy
12"	1641	13.3	123.38
12"	2781	21.9	126.98
17"	2800	16.8	133.0
17"	2781	21.9	126.98
17"	3300	20.1	164.17
21"	4000	28	142.85
21"	5562	41.3	134.67`

Slimlite flushmount utilizing LED technology. Features a white acrylic lens. Suitable for a variety of applications: Corridors, entry ways, kitchens, offices, bedrooms and more

## Dimensions:

Model	Diameter	Depth
<b>LFM1312</b>	12.5"	3.0"
<b>LFM1317</b>	17"	3.6"
<b>LFM1321</b>	21"	4.0"

\*SFM kit adds 10.5" to overall height



We Ship to the U.S.A.



## ORDERING INFORMATION

Example: LFM1312-1641L-30-WH-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
<b>LFM1312</b>	1641L – 13.3w, 1641L	30K – 3000K	WH – white	UNV – 120/277v Triac dimming
		35K – 3500K	BN – brushed nickel	277 – 277v Triac dimming
<b>LFM1317</b>	2800L – 16.8w; 2800L 2781L – 21.9w, 2781L 3300L – 20.1w; 3300L	40K – 4000K	PB – polished brass	347 – 347v Triac dimming
		50K – 5000K	CH – chrome	DM0-10 – 0-10V dimming
			BK – black	DALI – Dali dimming
<b>LFM1321</b>	4000L – 28w, 4000L 5562L – 41.3w, 5562L		CC – custom colour	EMB – emergency backup
			SFM-3-rod 10" pendant kit	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	