


Specifications:

- LED:** Philips
- CRI:** Min 80
- Body:** Steel
- Diffuser:** Acrylic – see options
- Finish:** See options
- Driver:** Standard 0-10v dimming
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** Damp location



“A” style trim



“B” style trim

Decorative acrylic surface mount utilizing LED technology. Fixture features choice of diffuser, trim style and finish options. Suitable for a variety of application: boardrooms, foyers, dining rooms and more

LED information:

Size	Lumens	Wattage	Efficacy
24"	3200	21.3	150.2
24"	4000	25.7	155.6
30"	4000	25.7	155.7
30"	4800	32.0	150.0
36"	4800	32.0	150.0
36"	5200	35.2	147.7

Dimensions:

Model	Diameter	Height
LFM2624	24"	8"
LFM2630	30"	8"
LFM2636	36"	8"

❖ “A” Style trim adds 1” to the diameter



We Ship to the U.S.A.



ORDERING INFORMATION

Example: LFM2630-4800L-35-A-WA-BN-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LFM2624	3200L – 3200L; 21.3w	30K – 3000K	<u>Trim</u>	UNV– 120/277Vv 0-10V dimming
	4000L – 4000L; 25.7w	35K – 3500K	A – A trim	347 – 347v 0-10 dimming
		40K – 4000K	B – B trim	DMTRC – 120/277v Triac dimming
LFM2630	4000L – 4000L; 25.7w	50K – 5000K	<u>Diffuser</u>	
	4800L – 4800L; 32.0w		WA – white acrylic	
LFM2636	4800L – 4800L; 32.0w		WFA – white faux alabaster	
			<u>Finish - cured</u>	<u>Finish –plated</u>
	5200L – 5200L; 25.2w		CBN – cured brushed nickel	PBN – brushed nickel plated
			CCH – cured chrome	PCH – chrome plated
			CAB – cured antique brass	PAB – antique brass plated
		CORB – cured oil rubbed bronze	PORB – oil rubbed bronze plated	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	