

LFM29

Specifications:



LED: Samsung S561B mid power LED
CRI: Min 80
Body: Steel
Diffuser: White acrylic, polycarbonate
Finish: See options
Driver: Standard Triac dimming; 0-10v available
Mounting: Directly to standard J-box
Warranty: 5 year on LED module/driver
Listing : Dry location



LED information:

| Size | Wattage | Lumens | Efficacy |
|------|---------|--------|----------|
| 13" | 12.4 | 1575 | 127.0 |
| 16" | 14 | 1750 | 125.0 |
| 16" | 21 | 2835 | 135.0 |
| 19" | 21 | 2835 | 135.0 |
| 19" | 28 | 3500 | 125.0 |

Large trimmed flushmount utilizing LED technology. Fixture features large trim in two designs. Suitable for a variety of applications: Corridors, entry ways, kitchens, offices, bedrooms and more

Dimensions:

| Model | Diameter | Depth |
|---------|----------|-------|
| LFM2913 | 13" | 5.5" |
| LFM2916 | 16" | 5.5" |
| LFM2919 | 19" | 5.5" |



We Ship to the U.S.A.



ORDERING INFORMATION

Example: LFM2916-21-40-WA-BN-SE-120

| MODEL # | LED MODULE | KELVIN | OPTIONS | VOLTAGE |
|---------|--|--------------------------|---------------------|--------------------------|
| LFM2913 | 12.4 – 12.4w, 1575L, 127.0 lm/w | 30 – 3000K | LENS | 120 – 120v Triac dimming |
| | | | WA – white acrylic | 277 – 277v Triac dimming |
| LFM2916 | 14 – 14w, 1750L, 125.0 lm/w 21 – 21w, 2835L, 135.0 lm/w | 40 – 4000K 50 – 5000K | P – polycarbonate | 347 – 347v Triac dimming |
| | | | FINISH | DM0-10 – 0-10V dimming |
| LFM2919 | 21 – 21w, 2835L, 135.0 lm/w 28 – 28w, 3500L, 125.0 lm/w | | BN – brushed nickel | |
| | | | BC – brushed chrome | |
| | | | PB – polished brass | |
| | | | WH – white | |
| | | | BK – black | |
| | | | TRIM | |
| | | | SE – stepped edge | |
| | | | SM – smooth edge | |



OVAL brand is manufactured by:
 Visioneered Lighting Mfg. Ltd.

www.ovallighting.com

| | | | |
|----------|--|---------|--|
| Job Name | | | |
| Type | | | |
| Part # | | | |
| Lamping | | Voltage | |