

## Specifications:



**LED:** Samsung / Philips mid power LED

**CRI:** Min 80

**Body:** White Steel

**Diffuser:** Acrylic, see options

**Finish:** see options

**Driver:** Standard 0-10v dimming

**Mounting:** Directly to standard J-box

**Warranty:** 5 year on LED module/driver

**Listing :** Damp location



“A” No cage      “B” Flat Bars      “C” Square tubing      “D” Vertical Tubing

## LED information:

Size	Wattage	Lumens	Efficacy
12"	7.2	1100	152.7
18"	13.3	1650	124.0
24"	15.2	2400	157.8
30"	19.7	3000	152.2
36"	22.8	3600	157.8

Economy wall sconce utilizing LED technology. Fixture features an acrylic lens with options for accent banding. Suitable for a variety of applications: corridors, living rooms; foyers, vanities and more

**Dimensions:** -cages “C” & “D” add ½” to all dimensions

Model	Height	Width	Projection
LWMA1912	12"	9.25"	4"
LWMA1918	16"	10"	4"
LWMA1924	24"	10"	4"
LWMA1930	30"	10"	4"
LWMA1936	36"	10"	4"



## ORDERING INFORMATION

Example: LWMA1924-2400L-40K-WA-CBN-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LWMA1912	1100L – 7.2w; 1100L	30K – 3000K 35K – 3500K	<u>LENS</u> WA – white acrylic	UNV– 120/277Vv 0-10v 347 – 347v 0-10v
LWMA1918	1650L – 13.3w; 1650L	40K – 4000K 50K – 5000K	WFA – white faux alabaster <u>FINISH-cured</u>	*consult for Triac dimming
LWMA1924	2400L – 15.2w; 2400L		CBN – cured brushed nickel CAB – cured antique brass	<u>FINISH - plated</u> PBN – plated brushed nickel
LWMA1930	3000L – 19.7w; 3000L		CCH – cured chrome CWH – cured white	PAB – plated antique brass PCH – plated chrome
LWMA1936	3600L – 22.8w; 3600L		CORB – cured oil rubbed bronze	PORB – plated oil rubbed bronze



Job Name			
Type			
Part #			
Lamping		Voltage	

www.ovallighting.com