

LWMA49

Specifications:



- LED:** Philips
- CRI:** Min 80
- Body:** Steel
- Diffuser:** Acrylic, see options
- Finish:** Brushed nickel
- Driver:** Standard Triac dimming; 0-10v dimming available
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** Damp location



LED information:

Size	Wattage	Lumens	Efficacy
12"	6.8	1100	161.7
12"	10.2	1650	161.7

*based on 4000K

Decorative rectangular wall sconce utilizing LED technology. Accented with wide half height frame. Fixture features choice of diffuser. Suitable for a variety of applications: corridors, bathrooms, foyers and more

Dimensions:

Model	Height	Width	Projection
LWMA4912	12.25"	8.5"	4"



ORDERING INFORMATION

Example: LWMA4912-10.2-40-WA-BN-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LWMA4912	6.8 – 6.8w; 1100L	30 – 3000K	LENS	UNV – 120/277v Triac dimming
	10.2 – 10.2w, 1650l	35 – 3500K	WA-white acrylic	347 – 347v 0-10v dimming
		40 – 4000K	WFA-white faux alabaster	DM0-10 – 120/277v 0-10V dimming
		50 – 5000K	FINISH	
			BN-brushed nickel	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	