

LWMA70

Specifications:

- LED:** Philips
- CRI:** Min 80
- Body:** White Steel
- Diffuser:** Acrylic, see options
- Finish:** see options
- Driver:** Standard Triac dimming; 0-10v dimming available
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** Damp location



LED information:

Size	Wattage	Lumens	Efficacy
15"	9.6	1600	166.66
15"	16.5	2400	145.45

*based on 4000K

Decorative rectangular wall sconce utilizing LED technology. Accented with deco frame. Fixture features choice of diffuser and finish. Suitable for a variety of applications: corridors, bathrooms, foyers and more

Dimensions:

Model	Height	Width	Projection
LWMA7015	15"	10"	4"



ORDERING INFORMATION

Example: LWMA7015-16.5-40-WA-BN-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LWMA7015	9.6 – 9.6w, 1600L	30 – 3000K	LENS	UNV – 120/277v Triac dimming
	16.5 – 16.5w, 2400L	35 – 3500K	WA-white acrylic	347 – 347v 0-10v dimming
		40 – 4000K	WFA-white faux alabaster	DM0-10 – 120/277v 0-10V dimming
		50 – 5000K	FINISH	
			BN-brushed nickel	
			AB-antique brass	
			CH-chrome	
			WH-white	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	