

OD-4



A practical and economical entry fixture manufactured from a durable, polycarbonate housing.

SPECIFICATIONS

Max Watt: 13W
Body: Polycarbonate
Trim: Polycarbonate
Finish: Black or White
Diffuser: Acrylic or Polycarbonate
Lamps: **Q** Quad Tube - 4 Pin, **T** Triple Tube - 4 Pin, **TT** Twin Tube - 2 Pin
Ballast: 4 Pin - Electronic; 2 Pin - Magnetic



Fixture Type	Model No	Job Reference /Location	Lamp Type/Lamp

Model	Lamps	Watts/Lamp	Ballast	Options
OD-4-DL	1	13W TT	N-NPF	AC- ACRYLIC
OD-4-CF	1	13Q	F-HPF	PC- POLYCARBO NATE
			E- ELECTRONIC	T25, T25CL
			ED- DIMMING	G40 (QUAD LAMP)
			V2-277V	

Model	Width	Max Watt	Depth/Proj.	
OD-4-DL	4.45"	13W	5.75"	Ballasts: 120V, fixtures supplied with NPF magnetic, HPF magnetic, HPF high frequency electronic ballasts. Mechanical: Fixtures mount directly to an outlet box. Approval: CSA NRTL/C
OD-4-CF	4.75"	13W	2"	