

Specifications:

- LED:** Samsung / Philips mid power LED
- CRI:** Min 80
- Body:** Steel / epoxy powder coatin – 34Wg
- Diffuser:** polycarbonate
- Finish:** White
- Driver:** 120/277v
- Mounting:** Medium base recessed housing / standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** Damp location



LED information:


Size	Wattage	Lumens	Efficacy
13"	34	2750	80.8

LED decorative square retrofit designed to convert recessed downlight to surface mount or mount to standard j-box. Polycarbonate shade provides resistant to damage. Suitable for a variety of applications: corridors, entry ways, and more

Dimensions:

Model	Length	Width	Height
LFM4713*	13.8"	13.0"	3.6"

*Energy Star certified without adaptor only



Optional adaptor



We Ship to the U.S.A.

ORDERING INFORMATION

Example: LFM4713-34-40-UNV

5 year warranty on LED parts and components

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LFM4713	34 – 34w; 2750L	30 – 3000K* 40 – 4000K	ADPT – medium base adaptor	UNV– 120/277Vv
		*non-stock – minimum qty req'd – 90+ days delivery		



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	