



Flush mount utilizing LED technology. Features a white acrylic lens. Suitable for a variety of applications: Corridors, entry ways, kitchens, offices, bedrooms and more

Specifications:

LED: Samsung 2323 or Philips Fortimo
Body: Steel
Finish: Powder coated gloss white housing
Mounting: Directly to standard J-box
Listing : Dry location

CRI: MIN 80+
Diffuser: See options
Driver: Standard Triac dimming; 0-10v available
Warranty: 5 year on LED module/driver

LED information:

Size	Wattage	Lumens	Efficacy
11"	10.3	1236	120.0
11"	13.3	1641	123.3
14"	13.3	1641	123.3
14"	13.4	2200	164.1
14"	21.9	2781	126.9
19"	21.9	2781	126.9
19"	20.1	3300	164.1
19"	28.0	4000	142.8

*rated lumens @ 5000K

Dimensions:

Model	Diameter	Depth
LFM1611	11"	3.2"
LFM1614	14"	3.6"
LFM1619	19"	4.0"



We Ship to the U.S.A.



ORDERING INFORMATION

Example: LFM1614-19.1-30-WA-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LFM1611	10.3 – 10.3w, 1236L	30 – 3000K	WA – white acrylic	UNV – 120/277v Triac dimming
	13.3 – 13.3w; 1641L	35 – 3500K	PA – prismatic acrylic	347 – 347v Triac dimming
		40 – 4000K	P – polycarbonate	DM0-10 – 0-10v dimming
LFM1614	13.3– 13.3w, 1641L	50 – 5000K	T – tamper proof	
	13.4 – 13.4w, 2200L			
	21.9 – 21.9w, 2781L			
LFM1619	21.9 – 21.9w; 2871L			NOTE: THE 11" 347V HAVE THE FOLLOWING CONFIGURATIONS:
	20.1 – 20.1w, 3300L			6.8W FOR 1100 LUMENS
	28.0 – 28w, 4000L			10.2 FOR 1650 LUMENS
				Ex: LFM1611-6.8-30-WA-347



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	