

Specifications:



- Body:** Steel
- Diffuser:** White acrylic or polycarbonate
- Finish:** Powder coated gloss white back pan
- Ballast:** Electronic, 120v, 277v, 347v, UNV (120/277v)
- Mounting:** Directly to standard J-box
- Warranty:** 1 year
- Listing :** Damp location



Maximum wattage information:

Size	Max Wattage
11"	26w
14"	52w
19"	78w

Low profile fixture available in three sizes and many compact fluorescent lamp configurations. Also available with polycarbonate lens and tamper proof options. Suitable for a variety of applications: Corridors, entry ways, kitchens, offices, bedrooms, dorms and more

Dimensions:

Model	Diameter	Depth
CM18-11	11"	3.5"
CM18-14	14"	3.6"
CM18-19	19"	4.0"



We Ship to the U.S.A.



ORDERING INFORMATION

Example: CM18-14-2-26Q-WA -UNV

MODEL #	LAMPS	WATTAGE	OPTIONS	BALLAST
CM18-11	1	13TT – 13w mag twin tube	WA – white acrylic	M(X) – magnetic, (N) NPF, (F) HPF
CM18-14	2	13Q – 13w electronic quad tube	P – polycarbonate	UNV – 120/277v
CM18-19	3	18Q – 18w electronic quad tube	T – tamper proof	347 – 347v
		26Q – 26w electronic quad tube	ALUM – aluminum body	DMADV MK10 – Advance Mark 10 2-wire dimming
		32T – 32w electronic triple tube	GSK – gasket	DMADV MK7 – Advance Mark 7 4-wire dimming
		42T – 42w electronic triple tube	SFM – semi-flush mount stem kit (6" rod)	

Legend: **TT** – twin tube magnetic; **Q** quad tube 4-pin electronic, **T** triple tube 4-pin electronic



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	