

Specifications:



- LED:** Samsung / Philips mid power LED
- CRI:** Min 80
- Body:** Steel
- Diffuser:** White acrylic or polycarbonate
- Finish:** White powder coat housing
- Driver:** Standard Triac dimming, (excluding 347v)
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** Dry location



LED information:

Size	Wattage	Lumens	Efficacy
11"	10.3	1236	120.0
11"	13.3	1641	123.3
14"	13.3	1641	123.3
14"	21.9	2781	126.9
19"	20.1	3300	164.1
19"	26.8	4400	164.1

A simple yet functional square flush mount utilizing LED technology. Features a white acrylic lens standard with a polycarbonate option. Available in three sizes with choice of lumen options. Suitable for a variety of applications: corridors, entry ways, kitchens, offices, bedrooms and more

Dimensions:

Model	Length	Width	Depth
LFM1512	12"	12"	2.63"
LFM1515	15"	15"	2.75"
LFM1519	19"	19"	2.88"



We Ship to the U.S.A.



ORDERING INFORMATION

Example: **LFM2011-13.3-30-WA-UNV**

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LFM2011	10.3 – 10.3w; 1236L	30 – 3000K	<u>LENS</u>	UNV– 120/277Vv Triac dimming
	13.3 – 13.3w; 1641L	35 – 3500K	WA – white acrylic	347 – 347v Triac dimming
		40 – 4000K	P – polycarbonate	0-10V – 0-10V dimming
LFM2015	13.3 – 13.3w; 1641L	50 – 5000K	<u>FINISH</u>	
	21.9 – 21.9w; 2781L		WH - white	
LFM2019			BN – brushed nickel	
	20.1 – 20.1w; 3300L			
	26.8 – 26.8w; 4400L		TP – tamper proof	



Job Name			
Type			
Part #			
Lamping		Voltage	