

Specifications:



LED: Samsung / Philips mid power LED

CRI: Min 80

Body: Steel

Diffuser: White acrylic

Finish: See options

Driver: Standard Triac dimming; 0-10v available (excluding 347v)

Mounting: Directly to standard J-box/ 2 x 72" field adjustable aircraft cable / lead provided

Warranty: 5 year on LED module/driver

Listing : Dry location



LED information:

Size	Wattage	Lumens	Efficacy
18"	10.2	1518	148.82
18"	24.2	3041	125.66
20"	24.2	3041	125.66
24"	24.2	3041	125.66

Decorative acrylic panel pendant utilizing LED technology. Available in three sizes and several LED packages. Suitable for a variety of application: dining rooms, board rooms, reception areas and more

Dimensions:

Model	Height	Diameter
LPM4918	18"	10"
LPM4920	20"	10"
LPM4924	24"	10"



We Ship to the U.S.A.



ORDERING INFORMATION

Example: LPM4918-10.2-40-WA-BN-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LPM4918	10.2 – 10.2w; 1518L	30 – 3000K	LENS	UNV – 120/277Vv Triac dimming
	24.2 – 24.2W; 3041L	35 – 3500K	WA – white acrylic	347 – 347v Triac dimming
		40 – 4000K	WFA – white faux alabaster	0-10V – 0-10V dimming
LPM4920	24.2 – 24.2W; 3041L	50 – 5000K	FINISH	
			AB – antique brass	
LPM4924	24.2 – 24.2W; 3041L		BN – brushed nickel	
			CH – chrome	
			ORB – oil rubbed bronze	
			WH - white	



Job Name			
Type			
Part #			
Lamping		Voltage	