

Specifications:

LED: Samsung / Philips mid power LED

CRI: Min 80

Body: Steel

Diffuser: See options

Finish: White hsg / see options for trim

Driver: Standard Triac dimming

Mounting: Directly to standard J-box

Warranty: 5 year on LED module/driver

Listing : Damp location



Cage 1



Cage 2

LED information:

Size	Wattage	Lumens	Efficacy
12"	6.8	1100	161.7
12"	13.4	2200	164.1

Decorative wall sconce utilizing LED technology. Choice of cage styles, lens, finish and lumen options. Suitable for a variety of applications: entry ways, corridors, offices, bathrooms and more

Dimensions:

Model	Height	Width	Depth
LFM1012	12.25"	8.125"	4"



We Ship to the U.S.A.



ADA Compliant



ORDERING INFORMATION

Example: LFM1012-14-30-WA-BN-CG1-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LWMA1012	6.8 – 6.8w, 1100L	30 – 3000K	LENS	UNV– 120/277Vv Triac dimming
	13.4 – 13.4w; 2200L	35 – 3500K	WA – white acrylic	347 – 347v non-dimming only
		40 – 4000K	WFA – white faux alabaster*	DMMK10 – 0-10V dimming, 2 wire
		50 – 5000K	FINISH	DMMK7 – 0-10v dimming, 4 wire
			PB – polished brass	
			BN – brushed nickel	
			AB – antique brass*	
			ORB – oil rubbed bronze	
			CAGE	
			CG1 – cage 1	
			CG2 – cage 2*	
			DC – dust covers (top & bottom)	
			*minimums may apply	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	