

## Specifications:



- Body:** Steel
- Diffuser:** See below
- Finish:** See below
- Ballast:** Electronic, 120v, 277v, 347v, UNV (120/277v)
- Mounting:** Directly to standard J-box
- Warranty:** 1 year
- Listing :** Dry location



## Maximum wattage information:

Size	Max Wattage
34"	168w
40"	192w

Modern three-tiered pendant. Choice of decorative stems. Two choices of lens finish and size, with several lamping variations. Suitable for a variety of applications: lobbies, reception areas; offices etc

## Dimensions:

Model	Diameter	Depth	Adj mount
CP34-34	34"	9"	Up to 30"
CP34-40	40"	9"	Up to 30"



We Ship to the U.S.A.



## ORDERING INFORMATION

Example: CP34-34-4-32T-WA-BN-SR/5R-UNV

MODEL #	LAMPS	WATTAGE	OPTIONS	BALLAST
CP34-34	1	26Q – 26w electronic quad tube	<b>LENS</b>	UNV – 120/277v
CP34-40	2	32T – 32w electronic triple tube	WA-white acrylic	347 – 347v
	3	42T – 42w electronic triple tube	WFA-white faux alabaster	DMADVMK10 – Advance Mark 10 2-wire
	4	27w – 27w electronic long	<b>FINISH</b>	DMADVMK7 – Advance Mark 7 4-wire
	5		BN – brushed nickel	PS-program start
	6		ORB – oil rubbed bronze	
			CH– chrome	
			CC-custom colour	
			<b>STEMS</b>	
			SR – single rod	
			3R – three rods	
			SR/5R-single rod/5 rods from bowl to stem	
			SR/AC-single rod/air craft cable from bowl to stem	

Legend: LTT – long twin tube 4-pin electronic; Q quad tube 4-pin electronic, T triple tube 4-pin electronic



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	