

Specifications:



LED: Samsung / Philips mid power LED
CRI: Min 80
Body: Steel
Diffuser: Opal acrylic
Finish: White powder coat housing
Driver: 11" & 14" standard triac dimming;
 19" standard 0-10v dimming
Mounting: Directly to standard J-box
Warranty: 5 year on LED module/driver
Listing : Damp location



LED information:

Size	Wattage	Lumens	Efficacy
11"	10.3	1236	120.0
11"	13.3	1641	123.3
14"	13.3	1641	123.3
14"	21.9	2781	126.9
19"	20.1	3300	164.1
19"	26.8	4400	164.1

Square flush mount cloud puff utilizing LED technology. Two lens options in three sizes with choice of lumen options. Suitable for a variety of applications: corridors, entry ways, kitchens, offices, bedrooms and more

Dimensions:

Model	Length	Width	Depth
LFM1511	11"	11"	3.2"
LFM1514	14"	14"	3.4"
LFM1519	19"	19"	3.8"



ORDERING INFORMATION

Example: LFM1511-1236L-35K-WA-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LFM1511	1236L – 10.3w; 1236L	30K – 3000K	WA – white acrylic	UNV– 120/277Vv Triac dimming
	1641L – 13.3w; 1641L	35K – 3500K		347 – 347v Triac dimming
		40K – 4000K		0-10V – 0-10V dimming
LFM1514	1641L – 13.3w; 1641L	50K – 5000K		
	2781L – 21.9w; 2781L			
LFM1519	3300L – 20.1w; 3300L			
	4400L – 26.8w; 4400L			



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	