



Shallow flush mount utilizing LED technology. Features a white acrylic lens. Suitable for a variety of applications: Corridors, entry ways, kitchens, offices, bedrooms and more

Specifications:

LED: Samsung 2323 or Philips Fortimo
Body: Steel
Finish: Powder coated gloss white housing
Mounting: Directly to standard J-box
Listing : Damp location

CRI: MIN 80+
Diffuser: See options
Driver: Standard Triac dimming; 0-10v available
Warranty: 5 year on LED module/driver

LED information:

Size	Wattage	Lumens	Efficacy
11"	10.3	1236	120.0
11"	13.3	1641	123.3
14"	13.3	1641	123.3
14"	13.4	2200	164.1
14"	21.9	2781	126.9
19"	21.9	2781	126.9
19"	20.1	3300	164.1
19"	28.0	4000	142.8

*rated lumens @ 5000K

Dimensions:

Model	Diameter	Depth
LFM1811	11"	3.2"
LFM1814	14"	3.6"
LFM1819	19"	4.0"



We Ship to the U.S.A.



ORDERING INFORMATION

Example: LFM1814-2200-30K-WA-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LFM1811	1236L – 10.3w, 1236L	30K – 3000K	WA – white acrylic LED lens	UNV – 120/277v Triac dimming
	1641L – 13.3w; 1641L	35K – 3500K	PA – prismatic acrylic	347 – 347v Triac dimming
		40K – 4000K	P – polycarbonate	DM0-10 – 0-10v dimming
LFM1814	1641L – 13.3w, 1641L	50K – 5000K	T – tamper proof	
	2200L – 13.4w, 2200L			
	2781L – 21.9w, 2781L			
LFM1819	2871L – 21.9w; 2871L			*NOTE: THE 11" 347V HAVE THE FOLLOWING CONFIGURATIONS:
	3300L – 20.1w, 3300L			6.8W FOR 1100 LUMENS
	4000L – 28w, 4000L			10.2W FOR 1650 LUMENS
				Ex: LFM1611-1100-30K-WA-347



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	