

## Specifications:

- LED:** Samsung or Philips mid power LED
- CRI:** Min 80
- Body:** Polycarbonate
- Diffuser:** Polycarbonate
- Finish:** White or black base
- Driver:** Standard Triac dimming
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** Wet location



## Outdoor



A robust two piece, injection molded, polycarbonate housing and diffuser outdoor surface mount utilizing LED technology. Deep “mushroom” style dome diffuser. Available in two LED lumen packages. Suitable for a variety of applications: entry ways, walkway canopies and more

### LED information:

| Size | Lumens | Wattage | Efficacy |
|------|--------|---------|----------|
| 11"  | 1236   | 10.3    | 120.0    |
| 11"  | 1641   | 13.3    | 123.3    |

### Dimensions:

| Model   | Diameter | Depth |
|---------|----------|-------|
| LOD0811 | 11"      | 5.25" |



## ORDERING INFORMATION

Example: LOD0811-1236L-30K-WH-UNV

| MODEL # | LED MODULE           | KELVIN      | OPTIONS           | VOLTAGE                              |
|---------|----------------------|-------------|-------------------|--------------------------------------|
| LOD0811 | 1236L – 10.3w, 1236L | 30K – 3000K | <b>BASE</b>       | <b>UNV</b> – 120/277Vv Triac dimming |
|         | 1641L – 13.3w, 1641L | 35K – 3500K | <b>WH</b> – white | <b>347</b> – 347v Triac dimming      |
|         |                      | 40K – 4000K | <b>BK</b> – black | <b>0-10V</b> – 0-10V dimming         |
|         |                      | 50K – 5000K |                   |                                      |



www.ovallighting.com

|          |  |         |  |
|----------|--|---------|--|
| Job Name |  |         |  |
| Type     |  |         |  |
| Part #   |  |         |  |
| Lamping  |  | Voltage |  |