

Specifications:

LED: Samsung S561B mid power LED
CRI: Min 80
Body: Steel
Diffuser: polycarbonate
Finish: See options
Driver: Standard Triac dimming
Mounting: Directly to standard J-box
Warranty: 5 year on LED module/driver
Listing : Wet location



CROSS GUARD



OPEN GUARD

EYELID GUARD



Outdoor

VANDAL PROOF

Low profile outdoor surface mount utilizing LED technology. Features a polycarbonate lens options and choice of guards and finishes. Tamper proof screws. Suitable for a variety of applications: entry ways, walkway canopies and more

LED information:

Size	Lumens	Wattage	Efficacy
13"	1236	10.3	120.0
13"	1641	13.3	123.3
13"	2781	21.9	126.9

Dimensions:

Model	Diameter	Depth
LOD11 OP GUARD	13.183"	3.625"
LOD11 CG, EG GUARD	13.183"	4.0"

ORDERING INFORMATION

Example: LOD1113-1641L-30K-WT-BK-CG-UNV



MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LOD1113	1236L – 10.3w; 1236L	30K – 3000K	LENS	UNV– 120/277v Triac dimming
	1641L – 13.3; 1641L	35K – 3500K	CR – clear ribbed	347 – 347v Triac dimming
	2781L – 21.9w; 2781L	40K – 4000K	FR – frosted ribbed	0-10v – 0-10v dimming
		50K – 5000K	WT – white translucent	
			FINISH	
			WH – white finish	
			BK – black finish	TPS – tamper proof screw driver
			BZ – bronze finish	
			TI – titanium finish	
			GUARD	
			OP – open guard	
			CG – cross guard	
			EG – eyelid guard	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	