

## Specifications:

**LED:** Samsung / Philips mid power LED

**CRI:** Min 80

**Body:** Steel

**Diffuser:** White acrylic

**Finish:** See options

**Driver:** Standard Triac dimming

**Mounting:** Directly to standard J-box

**Warranty:** 5 year on LED module/driver

**Listing :** cULus; Damp location



Decorative acrylic cylinder pendant utilizing LED technology. Suitable for a variety of application: board rooms, reception areas, grand lobbies, dance halls and more.

## LED information:

Size	Wattage	Lumens	Efficacy
30"	27	4000	148.1
30"	33	5000	151.5
36"	33	5000	151.5
36"	36	6000	166.7
42"	27	4000	148.1
42"	33	5000	151.5
42"	55	7800	141.8



## Dimensions:

Model	Cylinder Height	Dia
LPM5030	30"	13"
LPM5036	36"	13"
LPM5042	42"	13"

## ORDERING INFORMATION

Example: LPM5036-33-40-WA-WH-UNV-OA60

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE	
LPM5030	27 – 27w; 4000L	30 – 3000K	<b>LENS</b>	<b>UNV</b> – 120/277Vv Triac dimming	
	33 – 33w; 5000L	40 – 4000K	<b>WA</b> – white acrylic	<b>347</b> – 347v Triac dimming	
			<b>WFA</b> – white faux alabaster	<b>0-10V</b> – 0-10V dimming	
LPM5036	33 – 33w; 5000L		<b>FINISH</b>		
	36 – 36w; 6000L		<b>PC</b> – polished chrome		
			<b>BN</b> – brushed nickel		
LPM5042	27 – 27w; 4000L		<b>BC</b> – brushed chrome	<b>PENDANT OPTIONS</b>	
			<b>PBN</b> – painted brushed nickel		<b>OAx</b> – specify custom overall height
			<b>PBZ</b> – painted bronze		<b>ACK48</b> – 48" aircraft cable & clear power cord
			<b>WH</b> – painted white		
			<b>DL</b> – down light		



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	