

# LPM55

## Specifications:

- LED:** Philips
- CRI:** Min 80
- Body:** Steel
- Diffuser:** Acrylic – see options
- Finish:** See options
- Driver:** 120v/277v; 347v
- Dimming:** 0-10v standard
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** Damp location



Decorative pendant utilizing LED technology. Fixture features choice of three sizes, diffuser and finish options. Suitable for a variety of application: lobbies, boardrooms, foyers and more



### LED information: (downlight)

| Size | Wattage | Lumens | Efficacy |
|------|---------|--------|----------|
| 24"  | 21.4    | 3420   | 159.8    |
| 24"  | 30.3    | 4800   | 158.4    |
| 30"  | 30.3    | 4800   | 158.4    |
| 30"  | 33.3    | 5200   | 156.1    |
| 36"  | 33.3    | 5200   | 156.1    |
| 16"  | 37.8    | 5800   | 153.4    |

### LED information: (optional uplight)

| Size | Wattage | Lumens | Efficacy |
|------|---------|--------|----------|
| 24"  | 6.4     | 1000   | 156.2    |
| 30"  | 9.2     | 1500   | 163.4    |
| 36"  | 9.2     | 1500   | 163.4    |

### Dimensions:

| Model   | Diameter | Height |
|---------|----------|--------|
| LPM5524 | 24"      | 6"     |
| LPM5530 | 30"      | 8"     |
| LPM5536 | 36"      | 8"     |



## ORDERING INFORMATION

Example: LPM5530-4800L-1000L-40K-WA-BN-UNV-OAH30"

| MODEL # | LED MODULE                                   | UPLIGHT             | COLOUR TEMP                            | OPTIONS                                                  | VOLTAGE                                                |
|---------|----------------------------------------------|---------------------|----------------------------------------|----------------------------------------------------------|--------------------------------------------------------|
| LPM5524 | 3420L – 21.4w; 3420L<br>4800L – 30.3w; 4800L | 1000L – 6.4w; 1000L | 30 – 3000K<br>35 – 3500K<br>40 – 4000K | LENS<br>WA – white acrylic<br>WFA – white faux alabaster | UNV– 120/277Vv 0-10V<br>347 – 347v 0-10V               |
| LPM5530 | 4800L – 30.3w; 4800L<br>5200L – 33.3w; 5200L | 1500L – 9.2w; 1500L | 50 – 5000K                             | FINISH<br>BN - brushed nickel<br>AB – antique brass      | PENDANT                                                |
| LPM5536 | 5200L – 33.3w; 5200L<br>5800L – 37.8w; 5800L | 1500L – 9.2w; 1500L |                                        | CH – chrome<br>WH – white<br>ORB – oil rubbed bronze     | SFM – 10" SFM stem<br>OAHxx – overall height in inches |



www.ovallighting.com

|          |  |         |  |
|----------|--|---------|--|
| Job Name |  |         |  |
| Type     |  |         |  |
| Part #   |  |         |  |
| Lamping  |  | Voltage |  |