

LWMA15

Specifications:



- LED:** Samsung / Philips mid power LED
- CRI:** Min 80
- Body:** Steel
- Diffuser:** Acrylic – see options
- Finish:** See options
- Driver:** Standard Triac dimming (347V excluded)
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** Damp location



LED information:

Size	Wattage	Lumens	Efficacy
14"	6.8	1150	169.1
14"	10.2	1650	169.1
14"	14.0	2000	142.8
14"	13.4	2200	164.1

Economical wall sconce utilizing LED technology. Fixture features an acrylic lens with options for banding. Suitable for a variety of applications: corridors, living rooms; foyers and more

Dimensions:

Model	Height	Width	Projection
LWMA1514	7"	14"	3.6"



We Ship to the U.S.A.



ORDERING INFORMATION

Example: LWMA1514-14.0-40-WA-SBNB-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LWMA1514	1150L – 6.8w, 1150L	30K – 3000K	LENS	UNV – 120/277Vv Triac dimming
	1650L – 10.2w, 1650L	35K – 3500K	WA-white acrylic	347 – 347v 0-10V dimming
	2000L – 14w, 2000L	40K – 4000K	WFA-white faux alabaster	0-10V – 0-10V dimming
	2200L – 13.4w, 2200L	50K – 5000K	TRIMS	
			SxxB-single top band “xx” finish from below	
			DxxB-double top band “xx” finish from below	
			BN-brushed nickel	
			PB- polished brass	
			ORB-oil rubbed bronze	
			CH-chrome	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	