

LWMA26

Specifications:

- LED:** Philips mid power LED
- CRI:** Min 80
- Body:** Steel
- Diffuser:** Acrylic – see options
- Finish:** See options
- Driver:** Standard Triac dimming
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** Damp location



LED information:

Size	Wattage	Lumens	Efficacy
14"	6.8	1100	161.7
14"	10.2	1650	161.7
16"	6.7	1100	164.1
16"	13.4	2200	164.1

Decorative rectangular wall sconce utilizing LED technology. Fixture features choice of diffuser and finish options. Suitable for a variety of application: corridors, bathrooms, foyers and more

Dimensions:

Model	Height	Width	Projection
LWMA2612	14"	9.25"	4"
LWMA2616	16"	10"	4"



We Ship to the U.S.A.



ORDERING INFORMATION

Example: LWMA2614-1650L-30K-WA-CH-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LWMA2614	1100L – 6.8w, 1100L	30K – 3000K	LENS	UNV – 120/277Vv Triac dimming
	1650L – 10.2w, 1650L	35K – 3500K	WA – white acrylic	347 – 347v 0-10V dimming
		40K – 4000K	WFA – white faux alabaster	0-10V – 0-10V dimming
LWMA2616	1650L – 10.2w, 1650L	50K – 5000K	FINISH	
		2000L – 14.0w, 2000L	BN - brushed nickel	
	AB – antique brass			
	CH – chrome			
			WH – white	
			ORB – oil rubbed bronze	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	