

Specifications:

- LED:** Philips LED
- CRI:** Min 80
- Body:** Steel
- Diffuser:** Acrylic
- Finish:** See options
- Driver:** Standard Triac dimming; 0 – 10v available
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** cCSAus; Damp location



LED information:

Size	Lumens	Wattage	Efficacy
13"	1100L	6.8w	164.1
13"	1650L	10.2w	164.1
13"	2200L	13.6w	161.7
13"	2900L	18.7w	155.08

Rectangular wall sconce utilizing LED technology. Features decorative accent bars, choice of lens and finish options. Suitable for a variety of applications: entry ways, corridors, offices, living rooms and more

Dimensions:

Model	Height	Width	Depth
LWMA7213	7"	13"	4"



Made in Canada
We Ship to the U.S.A.



ADA Compliant



ORDERING INFORMATION

Example: LWMA7213-1650L-40K-WA-CCH-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LWMA7213	1100L – 6.8w, 1100L	30K – 3000K	LENS	UNV– 120/277Vv Triac dimming
	1650L – 10.2w, 1650L	35K – 3500K	WA – white acrylic	347 – 347v Triac dimming
	2200L – 13.6w; 2000L	40K – 4000K	WFA – white faux alabaster	0-10V – 0-10V dimming
	2900L – 18.7w; 2900L	50K – 5000K	FINISH-CURED	
			CBN – cured brushed nickel	
			CCH – cured chrome	
			CORB – cured oil rubbed bronze	
			CAB – cured antique brass	
			FINISH-PLATED	
			PBN – plated brushed nickel	
			PCH – plated chrome	
			PORB – plated oil rubbed bronze	
			PAB – plated antique brass	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	

