

## Specifications:

- LED:** Samsung S561B mid power LED
- CRI:** Min 80
- Body:** Steel
- Diffuser:** polycarbonate
- Finish:** See options
- Driver:** Standard Triac dimming
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** cCSAus; Wet location; Vandal resistant



## Outdoor Vandal resistant



### LED information:

Size	Lumens	Wattage	Efficacy
13"	1641L	13.3w	123.38
13"	2781L	21.9w	111.44

### Dimensions:

Model	Diameter	Depth
LOD13 OP GUARD	13.183"	7.52"
LOD13 CG, HEG, VEG GUARD	13.183"	7.89"

Marine grade round outdoor surface mount utilizing LED technology. Deep box for higher output. Features polycarbonate lens options and choice of guards and finishes. Vandal resistant – tamperproof screws included. Suitable for a variety of applications: entry ways, walkway canopies and more

### ORDERING INFORMATION

Example: LOD1313-2781L-30K-WT-BK-OP-UNV



Made in Canada

We Ship to the U.S.A.



US



MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LOD1313	1641L – 13.3w, 1641L 2781L – 21.9w, 2781L	30K – 3000K	<b>LENS</b>	UNV– 120/277Vv Triac dimming
		35K – 3500K	CR – clear ribbed	347 – 347v Triac dimming
		40K – 4000K	FR – frosted ribbed	0-10V – 0-10V dimming
		50K – 5000K	WT – white translucent	
			<b>FINISH</b>	
			WH – white finish	
			BK – black finish	
			BZ – bronze finish	
			TI – titanium finish	
			<b>GUARD</b>	
			OP – open guard	
			CG – cross guard	
			EG – eyelid guard	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	