Specifications:



LED: Samsung mid power LED

CRI: Min 80 Body: Steel

Diffuser: Frosted glass **Finish:** Brushed nickel

Driver: Standard Triac dimming; 0-10v available

Mounting: Directly to standard J-box **Warranty:** 5 year on LED module/driver

Listing: cCSAus; Damp location



LED information:

Size	Lumens	Wattage	Wattage Efficacy	
14"	1641L	13.3	123.3	
14"	2781L	21.9	126.9	

Decorative semi-flush bowl pendant utilizing LED technology. Fixture features choice lumen modules. Suitable for a variety of applications: reception, dining; office etc

Dimensions:

Model	Dia	Height
LPM1414	14.75"	12"









ORDERING INFORMATION

Example: LPM1414-1641L-35K-FG-BN-UNV

MODEL#	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LPM1414	1641L – 1641L; 13.3w	30K – 3000K	DIFFUSER	UNV- 120/277Vv Triac dimming
	2781L – 2781L; 21.9w	35K – 3500K	FG – frosted glass	347 – 347V 0-10V dimming
		40K – 4000K		0-10V – 0-10V dimming
		50K – 5000K	<u>FINISH</u>	
			BN – brushed nickel	



www.ovallighting.com

Job Name			
Туре			
Part #			
Lamping		Voltage	