

# LPM57

## Specifications:



- LED:** Samsung mid power LED
- CRI:** Min 80
- Body:** Steel
- Diffuser:** Acrylic drum & white acrylic diffuser
- Finish:** See options
- Driver:** Standard Triac dimming; 0-10v available
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** cCSAus; Damp location



## LED information:

Size	Lumens	Wattage	Efficacy
12"	1236L	10.3w	120.0
12"	1641L	13.3w	123.3
14"	1641L	13.3w	123.3
14"	2781L	21.9w	126.9
16"	1641L	13.3w	123.3
16"	2781L	21.9w	126.9

Decorative semi-flush drum pendant utilizing LED technology. Fixture features choice of finish and lumen modules. Suitable for a variety of application: reception, dining; office etc

## Dimensions:

Model	Dia	Height
LPM5712	12.25"	9.5"
LPM5714	14.25"	9.5"
LPM5716	16.25"	9.5"



Made in Canada

We Ship to the U.S.A.



## ORDERING INFORMATION

Example: LPM5714-2781L-35K-WA-BNMYL-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LPM5712	1236L – 1236L; 10.3w	30K – 3000K	<b>DRUM</b>	UNV – 120/277Vv Triac dimming
	1641L – 1641L; 13.3w	35K – 3500K	WA – white acrylic	347 – 347V 0-10V dimming
		40K – 4000K	WFA – white faux alabaster acrylic	0-10V – 0-10V dimming
LPM5714	1641L – 1641L; 13.3w	50K – 5000K	BFA – beige faux alabaster acrylic	
	2781L – 2781L; 21.9w		<b>FINISH</b>	
LPM2716	1641L – 1641L; 13.3w		BNMYL – brushed nickel mylar rings	
	2781L – 2781L; 21.9w		BNMET – brushed nickel metal rings	
			ORBMET – oil rubbed bronze metal	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	