

Specifications:



- LED:** Samsung 2323 mid power LED
- CRI:** Min 80
- Body:** White Steel
- Diffuser:** Acrylic, see options
- Finish:** see options
- Driver:** Standard Triac dimming; 0-10v dimming available
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing:** Damp location



LED information:

Size	Wattage	Lumens	Efficacy
12"	6.8	1100	161.76
12"	10.2	1650	161.76
12"	13.6	2200	161.76

*based on 4000K

Decorative rectangular wall sconce utilizing LED technology. Choice of accents with double bars, full perf or centre perf. Fixture features choice of diffuser and finish. Suitable for a variety of applications: corridors, bathrooms, foyers and more

Dimensions:

Model	Height	Width	Projection
LWMA2412	11.5"	10"	3.875"



ORDERING INFORMATION

Example: LWMA2412-1650L-40-WA-BN-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LWMA2412	1100L – 6.8w, 1100L	30 – 3000K	LENS	UNV – 120/277v Triac dimming
	1650L – 10.2w, 1650L	35 – 3500K	WA-white acrylic	347 – 347v Triac dimming
	2200L – 13.6w, 2200L	40 – 4000K	WFA-white faux alabaster	DM0-10 – 0-10V dimming
		50 – 5000K	FINISH	
			BN-brushed nickel	
			AB-antique brass	
			CH-chrome	
			WH-white	
			Accent	
			CDB – centre double bar	
			FPERF – full perf	
			CPERF – centre perf	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	