

## Specifications:

- LED:** Philips mid power LED
- CRI:** Min 80
- Body:** Steel
- Diffuser:** Acrylic
- Finish:** See options
- Driver:** 0-10V dimming standard
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** cCSAus; Damp location



Decorative pendant utilizing LED technology. Available in five sizes and several LED packages. Decorative 3-rod pendant stem available in choice of finishes. Suitable for a variety of application: dining rooms, board rooms, reception areas and more

## LED information:

Size	Lumens Up/Down	Wattage Up/Down	Efficacy Up/Down
24"	600L/4000L	4.5W/23.3W	133.3/171.6
24"	900L/6000L	6.1W/35.3W	147.5/169.9
24"	1320L/8800L	7.5W/47.2W	176.0/186.4
30"	1320L/8800L	7.5W/47.2W	176.0/186.4
30"	1650L/11,000L	9.9W/58.8W	166.6/187.0
36"	1650L/11,000L	9.9W/58.8W	166.6/187.0
36"	2400L/16,000L	14.8W/86.8W	162.1/184.3
42"	2400L/16,000L	14.8W/86.8W	162.1/184.3
42"	3600L/24,000L	22.4W/137.8W	160.7/174.1
48"	2400L/16,000L	14.8W/86.8W	162.1/184.3
48"	3600L/24,000L	22.4W/137.8W	160.7/174.1

## Dimensions:

Model	Dia	Height
LPM2024	24"	10"
LPM2030	30"	10"
LPM2036	36"	12"
LPM2042	42"	12"
LPM2048	48"	12"



## ORDERING INFORMATION

Example: LPM2036-1650L/11000L-35K-WA-CBN-OAH36-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LPM2024	600L/4000L – 600L up/4000L down	30K – 3000K	<b>DIFFUSER</b>	UNV – 120/277Vv (0-10v)
	900L/6000L – 900L up/6000L down	35K – 3500K	WA – white acrylic	347 – 347v (0-10v)
	1320L/8800L – 1320L up/8000L down	40K – 4000K	WFA – white faux alabaster	
			WSA – white sanded acrylic	
LPM2030	1320L/8800L – 1320L up/8000L down		<b>FINISH-cured</b>	<b>FINISH-plated</b>
	1650L/11000L – 1650L up/11,000L down		CAB – cured antique brass	ABP – plated antique brass
LPM2036	1650L/11000L – 1650L up/11,000L down		CBN – cured brushed nickel	BNP – plated brushed nickel
			CCH – cured chrome	CHP – plated chrome
	2400L/16000L – 2400L up/16,000L down		CORB – cured oil rubbed bronze	ORBP – plated oil rubbed bronze
			CPB – cured polished brass	PBP – plated polished brass
LPM2042	2400L/16000L – 2400L up/16,000L down		<b>PENDANT</b>	
	3600L/24000L – 3600L up/24,000L down		OAHxx – overall height (inches)	
LPM2048	2400L/16000L – 2400L up/16,000L down			
	3600L/24000L – 3600L up/24,000L down			

\*uplight subject to change based on overall height



Job Name			
Type			
Part #			
Lamping		Voltage	