

Specifications:

LED: Samsung / Philips mid power LED

CRI: Min 80

Body: White Steel

Diffuser: Acrylic, see options

Finish: see options

Driver: Standard 0-10v dimming

Mounting: Directly to standard J-box

Warranty: 5 year on LED module/driver

Listing : Damp location



“A” No cage “B” Flat Bars “C” Square tubing “D” Vertical Tubing

LED information:

Size	Lumens	Wattage	Efficacy
14"	1650L	10.5w	157.1
14"	2000L	13.4w	149.2
18"	1650L	10.5w	157.1
18"	2000L	13.4w	149.2
24"	2400L	15.2w	157.8
30"	3000L	19.7w	152.2
36"	3600L	22.8w	157.8

Economy wall sconce utilizing LED technology. Fixture features an acrylic lens with options for accent banding. Suitable for a variety of applications: corridors, living rooms; foyers, vanities and more

Dimensions: -cages “C” & “D” add ½” to all dimensions

Model	Height	Width	Projection
LWMA1914	14"	5.15"	4"
LWMA1918	18"	5.15"	4"
LWMA1924	24"	5.15"	4"
LWMA1930	30"	5.15"	4"
LWMA1936	36"	5.15"	4"



ORDERING INFORMATION

Example: LWMA1924-2400L-40K-WA-CBN-UNV

MODEL #	LED MODULE	STYLE	KELVIN	OPTIONS	VOLTAGE
LWMA1914	1650 – 10.2w; 1600L	A	30K – 3000K	<u>LENS</u>	UNV– 120/277Vv 0-10v
	2000L – 13.4w; 2000L	B	35K – 3500K	WA – white acrylic	347 – 347v 0-10v
LWMA1918	1650L – 13.3w; 1650L	C	40K – 4000K	WFA – white faux alabaster	*consult for Triac dimming
	2000L – 13.4w; 2000L	D	50K – 5000K	<u>FINISH-cured</u>	
LWMA1924	2400L – 15.2w; 2400L			CBN – cured brushed nickel	<u>FINISH - plated</u>
				CAB – cured antique brass	PBN – plated brushed nickel
LWMA1930	3000L – 19.7w; 3000L			CCH – cured chrome	PAB – plated antique brass
				CWH – cured white	PCH – plated chrome
LWMA1936	3600L – 22.8w; 3600L			CORB – cured oil rubbed bronze	PORB – plated oil rubbed bronze



Job Name			
Type			
Part #			
Lamping		Voltage	

www.ovallighting.com