



Specifications:

LED: Samsung / Philips mid power LED

CRI: Min 80

Body: Steel

Diffuser: Acrylic

Finish: See options

Driver: Standard Triac dimming

Mounting: Directly to standard J-box

Warranty: 5 year on LED module/driver

Listing : Damp location



LED information:

Size	Lumens	Wattage	Efficacy
11"	1100	6.8	161.76
11"	1650	10.2	161.76
11"	2200	13.6	161.76

A decorative wall sconce utilizing LED technology available with two diffuser options and multiple finishes. Decorative bands accent the diffuser. Accepts LED CFL lamps. Suitable for a variety of applications: entry ways, corridors, offices, living rooms and more

Dimensions:

Model	Height	Width	Depth
LWMA2511	11.5"	9.25"	4"

ORDERING INFORMATION

Example: LWMA2511-1650K-30K-WA-CBN-UNV



MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LWM25711	1100L –1100L, 6.8w,	30K – 3000K	<u>LENS</u>	UNV– 120/277Vv Triac dimming
	1650L –1650L, 10.2w,	35K – 3500K	WA – white acrylic	347 – 347v Triac dimming
	2200L –2200L, 13.6w,	40K - 4000K	WFA – white faux alabaster	0-10V – 0-10V dimming
			<u>FINISH-CURED</u>	
			CBN – cured brushed nickel	
			CCH – cured chrome	
			CORB – cured oil rubbed bronze	
			CAB – cured antique brass	
			CRST – cured rust	
			<u>FINISH-PLATED</u>	
			PBN – plated brushed nickel	
			PCH – plated chrome	
			PORB – plated oil rubbed bronze	
			PAB – plated antique brass	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	