

LFM49

Specifications:

LED: Samsung / Philips mid power LED
CRI: Min 80
Body: Steel
Shade/Diffuser: Acrylic
Finish: See options
Driver: Standard 0-10v dimming
Mounting: Directly to standard J-box
Warranty: 5 year on LED module/driver
Listing : cCSAus; Damp location



Decorative acrylic surface mount utilizing LED technology. Available in three sizes and several LED packages. Acrylic shade options available. Suitable for a variety of application: dining rooms, board rooms, reception areas and more

LED information:

Size	Wattage	Lumens	Efficacy
16"	21.9	2781	126.9
18"	21.9	2781	126.9
18"	20.1	3300	164.1
20"	20.1	3300	164.1
20"	28.0	4000	142.8
24"	20.1	3300	164.1
24"	28.0	4000	142.8
30"	28.0	4000	124.6
30"	29.0	4400	151.7

Dimensions:

Model	Dia	Height
LFM4916	16"	5"
LFM4918	18"	5"
LFM4920	20"	5"
LFM4924	24"	6"
LFM4930	30"	6"

ORDERING INFORMATION

Example: LFM4924-3000L-30K-WA-CBN-UNV



We Ship to the USA



MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LFM4916	2781L – 21.9W; 2781L	30K – 3000K	<u>Diffuser</u>	UNV– 120/277Vv 0-10v dimming
		35K – 3500K	WA-white acrylic	347 – 347v 0-10v dimming
LFM4918	2781L – 21.9W; 2781L 3300L – 20.1W; 3300L	40K – 4000K	WFA – white faux alabaster	
		50K – 5000K	WSA – white sanded acrylic	
LFM4920	3300L – 20.1W; 3300L 4000L – 28.0W; 4000L		<u>FINISH-cured</u>	
			CAB – cured antique brass	
			CBN – cured brushed nickel	
LFM4924	3300L – 20.1W; 3300L 4000L – 28W; 4000L		CCH – cured chrome	
			CORB – cured oil rubbed bronze	
			CPB – cured polished brass	
LFP4930	4000L – 28W; 4000L 4400L – 29W; 4400L		<u>FINISH-plated</u>	
			ABP – plated antique brass	
			BNP – plated brushed nickel	
			CHP – plated chrome	
			ORBP – plated oil rubbed bronze	
			PBP – plated polished brass	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	