

## Specifications:

- LED:** Samsung S561B mid power LED
- CRI:** Min 80
- Body:** Die cast marine grade aluminum
- Diffuser:** polycarbonate
- Finish:** See options
- Driver:** Standard Triac dimming
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** cCSAus; Wet location; Vandal resistant



## Outdoor Vandal resistant



### LED information:

Size	Lumens	Wattage	Efficacy
13"	1641L	13.3w	123.38
13"	2781L	21.9w	111.44
13"	5562L	41.3w	134.67

### Dimensions:

Model	Diameter	Depth
LOD13 OP GUARD	13.183"	7.52"
LOD13 CG, HEG, VEG GUARD	13.183"	7.89"

Marine grade round outdoor surface mount utilizing LED technology. Deep box for higher output. Features polycarbonate lens options and choice of guards and finishes. Vandal resistant – tamperproof screws included. Suitable for a variety of applications: entry ways, walkway canopies and more



### ORDERING INFORMATION

Example: LOD1313-2781L-30K-WT-BK-OP-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LOD1313	1641L – 13.3w, 1641L	30K – 3000K	LENS	UNV– 120/277Vv Triac dimming
	2781L – 21.9w, 2781L	35K – 3500K	CR – clear ribbed	347 – 347v 0-10v dimming
	5562L – 41.3w, 5562L	40K – 4000K	FR – frosted ribbed	DM0-10V – 0-10V dimming; 120/277V
		50K – 5000K	WT – white translucent	
			<b>FINISH</b>	
			WH – white finish	
			BK – black finish	
			BZ – bronze finish	
			TI – titanium finish	
			<b>GUARD</b>	
			OP – open guard	
			CG – cross guard	
			EG – eyelid guard	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	