

Specifications:



- LED:** Philips
- CRI:** Min 80
- Body:** Steel
- Diffuser:** Acrylic, see options
- Finish:** Brushed nickel
- Driver:** Standard Triac dimming; 0-10v dimming available
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing:** Damp location



LED information:

Size	Wattage	Lumens	Efficacy
12"	6.8	1100	161.7
12"	10.2	1650	161.7

*based on 4000K

Decorative rectangular wall sconce utilizing LED technology. Accented with wide half height frame. Fixture features choice of diffuser. Suitable for a variety of applications: corridors, bathrooms, foyers and more

Dimensions:

Model	Height	Width	Projection
LWMA4912	12.25"	8.5"	4"



We Ship to the U.S.A.



ORDERING INFORMATION

Example: LWMA4912-1650L-40-WA-BN-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LWMA4912	1100L – 6.8w; 1100L	30 – 3000K	<u>LENS</u>	UNV – 120/277v Triac dimming
	1650L – 10.2w, 1650L	35 – 3500K	WA-white acrylic	347 – 347v 0-10v dimming
		40 – 4000K	WFA-white faux alabaster	DM0-10 – 120/277v 0-10V dimming
		50 – 5000K	<u>FINISH</u>	
			BN-brushed nickel	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	