

LWMA51

Specifications:

LED: Philips LED
CRI: Min 80
Body: Steel
Diffuser: Acrylic
Finish: See options
Driver: 120/277v
Dimming: 1100L-2200L Triac dimming standard; 3300L-4400L 0-10v standard
Mounting: Directly to standard J-box
Warranty: 5 year on LED module/driver
Listing : cCSAus; Damp location



Rectangular wall sconce utilizing LED technology. Features decorative cage, choice of lens and finish options. Suitable for a variety of applications: entry ways, corridors, offices, living rooms and more

Dimensions:

LED information:

Size	Lumens	Wattage	Efficacy
16"	1100L	6.8w	164.1
20"	1100L	6.8w	164.1
20"	2200L	13.6w	161.7
24"	2200L	13.6w	161.7
24"	3300L	20.4w	161.7
30"	3300L	20.4w	161.7
30"	4400L	27.2w	161.7

Dimensions:

Model	Height	Width	Depth
LWMA5116	16"	8"	4"
LWMA5120	20"	8"	4"
LWMA5124	24"	8"	4"
LWMA5130	30"	8"	4"

ORDERING INFORMATION

Example: LWMA7213-1650L-40K-WA-CCH-UNV



MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LWMA5116	1100L – 6.8w, 1100L	30K – 3000K	<u>LENS</u>	UNV– 120/277Vv Triac dimming
		35K – 3500K	WA – white acrylic	347 – 347v 0-10V dimming
LWMA5120	1100L – 6.8w, 1100L 2200L – 13.6w; 2200L	40K – 4000K	WFA – white faux alabaster	0-10V – 0-10V dimming
		50K – 5000K	<u>FINISH-CURED</u>	
LWMA5124	2200L – 13.6w; 2200L 3300L – 20.4w; 3300L		CBN – cured brushed nickel	
			CCH – cured chrome	
			CORB – cured oil rubbed bronze	
			CAB – cured antique brass	
LWMA5130	3300L – 20.4w; 3300L 4400L – 27.2w; 4400L		<u>FINISH-PLATED</u>	OPTIONS:
			PBN – plated brushed nickel	EC – end caps
			PCH – plated chrome	
			PORB – plated oil rubbed bronze	
			PAB – plated antique brass	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	