

Specifications:

- Diffuser:** Acrylic
- Body:** Steel
- Finish:** See below
- Ballast:** Electronic, 120v, 277v, 347v, UNV (120/277v)
- Mounting:** Directly to standard J-box
- Dimming:** 0-10v option available
- Warranty:** 1 year
- Listing :** Dry location



Maximum wattage information:

Size	Max Wattage
11"	26w
14"	52w
19"	84w

Simple acrylic wall sconce with choice of diffuser, top band and lamping. Suitable for a variety of applications: Corridors, entry ways, offices, bathrooms and more

Dimensions:

Model	Height	Width	Depth
ADA1511	5.5"	11"	3.5"
ADA1514	7"	14"	3.6"
ADA1519	9.5"	19"	4"

ORDERING INFORMATION

Example: ADA1514-226Q-WA-UNV

MODEL #	# LAMPS	WATTAGE	OPTIONS	BALLAST
ADA1511	1	26Q – 26w quad 4-pin	<u>LENS</u>	UNV – 120/277V
ADA1514	2	26T – 26w triple tube 4-pin	WA – white acrylic	347 – 347v
ADA1519		32T – 32w triple tube 4-pin	WFA – white faux alabaster*	DMMK10– 0-10V dimming – 2 wire
		42T – 42w triple tube 4-pin	<u>TOP TRIM BAND</u>	DMMK7 0 0-10v dimming – 4 wire
		LMED – E26 base LED lamp	PBB – polished brass top band	
			BNB – brushed nickel top band	
			ABB – antique brass top band	
			ORBB – oil rubbed bronze top band	



Legend: **Q** quad tube 4-pin electronic, **T** triple tube 4-pin electronic, **LMED** 15w max A19 E26 base



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	