


# FLWMA10

## Specifications:

**LED:** Fulham  
**CRI:** Min 80  
**Body:** Steel  
**Diffuser:** See options  
**Finish:** White hsg / see options for trim  
**Driver:** Standard Triac dimming  
**Mounting:** Directly to standard J-box  
**Warranty:** 5 year on LED module/driver  
**Listing :** Damp location



Cage 1



Cage 2

## LED information:

Size	Wattage	Lumens	Efficacy
12"	9w	1518L	168.6
12"	12w	1800L	150.0

Decorative wall sconce utilizing LED technology. Choice of cage styles, lens, finish and lumen options. Suitable for a variety of applications: entry ways, corridors, offices, bathrooms and more

## Dimensions:

Model	Height	Width	Depth
LFM1012	12.25"	8.125"	4"

## ORDERING INFORMATION

Example: FLWMA1012-14-30-WA-BN-CG1-UNV



MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
FLWMA1012	1518L – 9w; 1518L	30K – 3000K	<b>CAGE</b>	UNV– 120/277Vv Triac dimming
	1800L – 12w; 1800L	35K – 3500K	CG1 – cage 1	347 – 347v 0-10v dimming**
		40K – 4000K	CG2 – cage 2*	DMMK10 – 0-10V dimming, 2 wire**
		50K – 5000K	<b>LENS</b>	DMMK7 – 0-10v dimming, 4 wire**
			WA – white acrylic	
			WFA – white faux alabaster*	
			<b>FINISH – (cured)</b>	<b>FINISH – (plated)</b>
			CPB – polished brass	PPB – polished brass
			CBN – brushed nickel	PBN – brushed nickel
			CAB – antique brass*	PAB – antique brass*
			CORB – oil rubbed bronze	PORB – oil rubbed bronze
			DC – dust cover (top only)	
			*minimums may apply	**consult factory for availability



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	