



Flush mount utilizing LED technology. Features a white acrylic lens. Suitable for a variety of applications: Corridors, entry ways, kitchens, offices, bedrooms and more

## Specifications:

**LED:** Samsung 2323 or Philips Fortimo  
**Body:** Steel  
**Finish:** Powder coated gloss white housing  
**Mounting:** Directly to standard J-box  
**Listing :** Dry location

**CRI:** MIN 80+  
**Diffuser:** See options  
**Driver** Triac dimming; 0-10v dimming\*\*  
**Warranty:** 5 year on LED module/driver

## LED information:

Size	Wattage	Lumens	Efficacy
11"	10.3	1236	120.0
11"	13.3	1641	123.3
14"	13.3	1641	123.3
14"	13.4	2200	164.1
14"	21.9	2781	126.9
19"	21.9	2781	126.9
19"	20.1	3300	164.1
19"	28.0	4000	142.8

\*rated lumens @ 5000K

## Dimensions:

Model	Diameter	Depth
LFM1611	11"	3.2"
LFM1614	14"	3.6"
LFM1619	19"	4.0"



We Ship to the U.S.A.



## ORDERING INFORMATION

Example: LFM1614-2200L-30K-WA-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LFM1611	1236L – 10.3w, 1236L*	30K – 3000K	WA – white acrylic LED lens	UNV – 120/277v Triac/0-10v**
	1641L – 13.3w; 1641L*	35K – 3500K	PA – prismatic acrylic***	347 – 347v 0-10v dimming
		40K – 4000K	P – polycarbonate	UNV0-10V – 0-10V dimming
LFM1614	1641L – 13.3w, 1641L*	50K – 5000K	T – tamper proof	
	2200L – 13.4w, 2200L*			
	2781L – 21.9w, 2781L**		MORBN – brushed nickel metal out ring	*NOTE: THE 11" 347V HAVE THE
LFM1619	2781L – 21.9w; 2781L**		MORWH – white metal out ring	FOLLOWING CONFIGURATIONS:
	3300L – 20.1w, 3300L**		SFM – 9" pendant stem for semi-flush	10.2W FOR 1650 LUMENS
	4000L – 28w; 4000L**			Ex: LFM1611-1100-30K-WA-347

\*ships with standard Triac dimming unless specified otherwise \*\*available in 0-10v dimming only \*\*\*not available in 19"



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	