

Specifications:



- LED:** Samsung / Philips mid power LED
- CRI:** Min 80
- Body:** Steel
- Trim:** Steel
- Diffuser:** White opal inner glass/clear glass outer
- Finish:** Chrome
- Driver:** 0-10v dimming standard; consult for triac dimming
- Mounting:** Directly to standard J-box; ships with 2 – 12” and 2 – 6” rods to adjust pendant stem length.
- Warranty:** 5 year on LED module/driver
- Listing:** Damp location

Decorative glass shade pendant utilizing LED technology. Available in two sizes and LED packages. Suitable for a variety of application: dining rooms, board rooms, reception areas and more.



LED information:

Size	Lumens	Wattage	Efficacy
16”	2600L/800L	15.9W/4.4W	163.5/181.8
18”	3000L/900L	17.6W/5.0W	170.4/180.0

Dimensions:

Model	Dia	Height
LPM2216	16”	7”
LPM2218	19.75”	7”

ORDERING INFORMATION

Example: LPM2216-2600L-35K-CH-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LPM2216	2600L – 2600L downlight only	30K – 3000K	FINISH	UNV– 120/277Vv 0-10v dimming
	2600L/800L – 2600L down/800L up	35K – 3500K	CH –chrome	347 – 0-10v dimming
		40K – 4000K		TRIAC – consult factory
LPM2218	3000L – 3000L downlight only	50K – 5000K		
	3000L/900L – 3000L down/900L up			



Job Name			
Type			
Part #			
Lamping		Voltage	