

LPM55

Specifications:

LED: Philips
CRI: Min 80
Body: Steel
Diffuser: Acrylic – see options
Finish: See options
Driver: 120v/277v; 347v
Dimming: 0-10v standard
Mounting: Directly to standard J-box
Warranty: 5 year on LED module/driver
Listing : Damp location



Decorative pendant utilizing LED technology. Fixture features choice of three sizes, diffuser and finish options. Canopy is suitable for sloped ceiling application. Suitable for a variety of application: lobbies, boardrooms, foyers and more



LED information: (downlight)

Size	Wattage	Lumens	Efficacy
24"	21.4	3420	159.8
24"	30.3	4800	158.4
24"	42.0	6600	157.1
30"	30.3	4800	158.4
30"	33.3	5200	156.1
30"	42.0	6600	157.1
36"	33.3	5200	156.1
36"	37.8	5800	153.4
36"	42.0	6600	157.1

LED information: (optional uplight)

Size	Wattage	Lumens	Efficacy
24"	6.4	1000	156.2
24"	20.1	3300	164.1
30"	9.2	1500	163.4
30"	20.1	3300	164.1
36"	9.2	1500	163.4
36"	20.1	3300	163.4

Dimensions

Model	Diameter	Height
LPM5524	24"	6"
LPM5530	30"	8"
LPM5536	36"	8"

ORDERING INFORMATION

Example: LPM5530-4800L-1000L-40K-WA-BN-UNV-OAH30"

MODEL #	LED MODULE	UPLIGHT	COLOUR TEMP	OPTIONS	VOLTAGE
LPM5524	3420L – 21.4w; 3420L	1000L – 6.4w; 1000L	30 – 3000K	LENS	UNV – 120/277V 0-10V
	4800L – 30.3w; 4800L	3300L – 20.1w; 3300L	35 – 3500K	WA – white acrylic	347 – 347v 0-10V
	6600L – 42.0w; 6600L		40 – 4000K	WFA – white faux alabaster	
LPM5530	4800L – 30.3w; 4800L	1500L – 9.2w; 1500L		FINISH	
	5200L – 33.3w; 5200L	3300L – 20.1w; 3300L		BN - brushed nickel	PENDANT
	6600L – 42.0w; 6600L			AB – antique brass	SFM – 10" SFM stem
LPM5536	5200L – 33.3w; 5200L	1500L – 9.2w; 1500L		CH – chrome	OAHxx – overall height in inches
	5800L – 37.8w; 5800L	3300L – 20.1w; 3300L		WH – white	
	6600L – 42.0w; 6600L			ORB – oil rubbed bronze	



Job Name			
Type			
Part #			
Lamping		Voltage	

www.ovallighting.com