

Specifications:

LED: Samsung / Philips mid power LED

CRI: Min 80

Body: Steel

Diffuser: N/A

Finish: See options

Driver: Standard Triac dimming

Mounting: Directly to standard J-box

Warranty: 5 year on LED module/driver

Listing : Damp location



UPLIGHT ONLY



LED information:

Size	Wattage	Lumens	Efficacy
12"	6.8	1100	161.7
12"	10.2	1650	161.7
16"	6.7	1100	164.1
16"	13.4	2200	164.1

All steel wall sconce utilizing LED technology provide ambient uplight. Fixture features steel body. The choice of colours make the possibilities endless. Suitable for a variety of applications: corridors, reception areas, living rooms, etc.

Dimensions:

Model	Height	Width	Projection
LWM1012	6.5"	12.25"	6.6"
LWM1016	6.5"	16.25"	6.6"



We Ship to the U.S.A.



ORDERING INFORMATION

Example: LWM1012-6.8-35-BN-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LWM1012	1100L – 6.8w, 1100L	30K – 3000K	FINISH	UNV – 120/277Vv Triac dimming
	1650L – 10.2w, 1650L	35K – 3500K	BN - brushed nickel	347 – 347v 0-10V dimming*
		40K – 4000K	AB – antique brass	0-10V – 0-10V dimming*
		50K – 5000K	CH – chrome	
LWM1016	1100L – 6.7w, 1100L		WH – white	
	2200L – 13.4w, 2200L		ORB – oil rubbed bronze	
			CC – custom colour	
				*consult for availability



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	