

Specifications:

- LED:** Samsung / Philips mid power LED
- CRI:** Min 80
- Body:** Steel
- Diffuser:** Acrylic – see options
- Finish:** See options
- Driver:** Standard Triac dimming
- Mounting:** Directly to standard J-box
- Warranty:** 5 year on LED module/driver
- Listing :** Damp location



LED information:

Size	Wattage	Lumens	Efficacy
14"	6.8	1100	161.7
14"	10.2	1650	161.7
14"	14.0	2000	161.7
16"	6.7	1100	164.1
16"	13.4	2200	164.1
16"	20.1	3300	164.1

Decorative rectangular wall sconce utilizing LED technology. Fixture features choice of diffuser and finish options. Suitable for a variety of application: corridors, bathrooms, foyers and more



We Ship to the U.S.A.



Dimensions:

Model	Height	Width	Projection
LWMA2614	14"	9.25"	4"
LWMA2616	16"	10"	4"

ORDERING INFORMATION

Example: LWMA2614-10.2-30-WA-CH-UNV

MODEL #	LED MODULE	KELVIN	OPTIONS	VOLTAGE
LWMA2614	6.8 – 6.8w, 1100L	30 – 3000K	LENS	UNV – 120/277Vv Triac dimming
	10.2 – 10.2w, 1650L	35 – 3500K	WA – white acrylic	347 – 347v Triac dimming
	14.0 – 14.0w, 2000L	40 – 4000K	WFA – white faux alabaster	0-10V – 0-10V dimming
LWMA2616		50 – 5000K	FINISH	
	6.7 – 6.7w, 1100L		BN - brushed nickel	
	14.0 – 14.0w, 2000L		AB – antique brass	
	20.1 – 20.1w, 3300L		CH – chrome	
			WH – white	
			ORBI – oil rubbed bronze	



www.ovallighting.com

Job Name			
Type			
Part #			
Lamping		Voltage	